

DIELECTRIC RESONATOR OSCILLATOR


SURFACE MOUNT MODEL: GSDRO1024-8XT

FREQUENCY


10.24 GHz

FEATURES:

- ▶ Gold Standard Series
- ▶ Extended Operating Temperature Range
- ▶ Exceptional Phase Noise Performance
- ▶ Small Size Surface Mount
- ▶ Lead Free RoHS Compliant




Phase Noise



SPECIFICATIONS

Frequency	10.24 GHz	
Tuning Voltage	1 - 15 VDC	
Bias Voltage	+8 VDC @ 26 mA (Max.)	
Output Power	0 dBm (Min.)	
Tuning Sensitivity	0.23 MHz/V (Typ.)	
Thermal Drift	1.3 ppm / °C (Typ.)	
Output Impedance	50 Ohms (Nom.)	
Harmonic Suppression	24 dBc (Typ.)	
Frequency Pulling	115 kHz (Typ. @ 1.75:1 VSWR)	
Frequency Pushing	115 kHz/V (Typ.)	
Tuning Port Capacitance	35 pF (Typ.)	
Phase Noise @ 25°C	Offset	dBc/Hz (Typ.)
	10 kHz	-122
	100 kHz	-147
	1 MHz	-165
	10 MHz	-167
Operating Temperature Range	-40 to +85 °C	

Package # 396-7



Absolute Maximum Ratings

Storage Temp. Range	-45 to +90 °C
Bias Voltage	+8.5 V
Tuning Voltage	+17 V
DC Voltage Applied to RF Out	±25 V

Notes:

1. Tuning of the mechanical screw can cause significant shifts in frequency and cause irreversible damage to the product. Warranty is void if tuning screw exceeds ±0.5 turn max.
2. Test data measured with bias voltage at +8V.
3. Specifications guaranteed at 10.24 GHz.



DIELECTRIC RESONATOR OSCILLATOR

SURFACE MOUNT MODEL: GSDRO1024-8XT

FREQUENCY

10.24 GHz

PERFORMANCE PLOTS





DIELECTRIC RESONATOR OSCILLATOR

SURFACE MOUNT MODEL: GSDRO1024-8XT

FREQUENCY

10.24 GHz

PERFORMANCE PLOTS




DIELECTRIC RESONATOR OSCILLATOR

SURFACE MOUNT MODEL: GSDRO1024-8XT

FREQUENCY

10.24 GHz



PERFORMANCE PLOTS