

90° HYBRID

CONNECTORIZED MODEL: DQK-100-1000S

FREQUENCY BANDWIDTH

100 - 1000 MHz

FEATURES:

- ▶ Ultra-Wide Bandwidth (10:1)
- ▶ Small Package Size
- ▶ Building Block For:
 - Power Amplifiers
 - Image Rejection Mixers
 - I & Q / SSB Modulators
 - Phase Shifters & More...



SPECIFICATIONS (Rev. A 08/25/11)

Frequency	100 - 1000 MHz	
Insertion Loss (dB) *	Typ.	Max.
	1.5	2.3
Amplitude Unbalance (dB)	Typ.	Max.
	0.8	1.8
Phase Unbalance (Deg.)	Typ.	Max.
	± 6	± 10
Isolation (dB)	Typ.	Min.
	23	16
Power Rating	1 Watt (Max.)	
Impedance	50 Ohms (Nom.)	
VSWR	1.6:1 (Typ)	
Operating Temperature Range	-40 to +85 °C	

* Insertion loss in excess of the theoretical 3 dB coupling.

Package #	113LF
-----------	-------

All Dimensions in inches (mm)

Tolerances: 2 PL.±0.030 inch. (0.762mm)
3 PL.±0.015 inch. (0.381mm)

THRU-HOLES (2 PLACES)

A - 1.250 inch. (31.75 mm)
 B - 1.250 inch. (31.75 mm)
 C - 0.750 inch. (19.05 mm)
 D - 0.375 inch. (9.525 mm)
 E - 1.000 inch. (25.4 mm)
 F - 1.000 inch. (25.4 mm)
 G - Ø0.136 inch. (3.45 mm)
 H - 0.625 inch. (15.875 mm)
 I - 0.625 inch. (15.875 mm)

Connector Type: SMA Female

PORT IDENTIFICATION			
Input	Isolated *	+90° Output	0° Output
1	2	3	4



* Terminate ISOLATED port with 50 ohms externally.

90° HYBRID CONNECTORIZED MODEL: DQK-100-1000S

FREQUENCY BANDWIDTH

100 - 1000 MHz

Data @ 25°C



PERFORMANCE PLOTS



90° HYBRID CONNECTORIZED MODEL: DQK-100-1000S

FREQUENCY BANDWIDTH

100 - 1000 MHz

Data @ 25°C

PERFORMANCE PLOTS




90° HYBRID

CONNECTORIZED MODEL: DQK-100-1000S

FREQUENCY BANDWIDTH

100 - 1000 MHz

Data @ 25°C



PERFORMANCE PLOTS