

90° HYBRID COUPLER



SYNSTRI[®] MODEL: MSQ1323G

WIDE BANDWIDTH

1300 - 2300 MHz

FEATURES:

- ▶ Synstrip Technology™
- ▶ Small Package Size, Surface Mount
- ▶ REL-PRO® Patented Technology
- ▶ Building Block For:
 - Power Amplifiers
 - Image Rejection Mixers
 - I & Q / SSB Modulators
 - Phase Shifters & More...



SPECIFICATIONS (Rev. A 07/14/26))

Frequency	1300 - 2300 MHz		
Insertion Loss (dB) *	Frequency (MHz)	Typ.	Max.
	1300 - 2300	0.31	0.50
	1550 - 2050	0.22	0.35
Amplitude Unbalance (dB)	Frequency (MHz)	Typ.	Min.
	1300 - 2300	1.1	1.5
	1550 - 2050	0.4	0.7
Phase Unbalance (Deg.)	Frequency (MHz)	Typ.	Min.
	1300 - 2300	0.9	4
	1550 - 2050	0.9	3


Isolation (dB)	Frequency (MHz)	Typ.	Min.
	1300 - 2300	21	15
	1550 - 2050	23	18
Power Rating	100 Watts Avg. (CW)		
Impedance	50 Ohms (Nom.)		
VSWR	Frequency (MHz)	Max.	
	1300 - 2300	1.40:1	
	1550 - 2050	1.40:1	
Operating Temperature Range	-55 to +85 °C		
* Is the average of the two coupling signals in excess of the 3 dB theoretical signal splitting			

90° HYBRID COUPLER

SYNSTRIIP® MODEL: MSQ1323G

WIDE BANDWIDTH

1300 - 2300 MHz





90° HYBRID COUPLER

SYNSTRIIP® MODEL: MSQ1323G

WIDE BANDWIDTH

1300 - 2300 MHz

Data @ 25°C



PERFORMANCE PLOTS



90° HYBRID COUPLER

SYNSTRIIP® MODEL: MSQ1323G

WIDE BANDWIDTH

1300 - 2300 MHz

Data @ 25°C



PERFORMANCE PLOTS


90° HYBRID COUPLER

SYNSTRIIP® MODEL: MSQ1323G

WIDE BANDWIDTH

1300 - 2300 MHz

Data @ 25°C



PERFORMANCE PLOTS