

90° HYBRID COUPLER



SYNSTRI[®] MODEL: MSQ4794M

WIDE BANDWIDTH

470 - 940 MHz

FEATURES:

- ▶ Synstrip Technology™
- ▶ Small Package Size, Surface Mount
- ▶ REL-PRO® Patented Technology
- ▶ Building Block For:
 - Power Amplifiers
 - Image Rejection Mixers
 - I & Q / SSB Modulators
 - Phase Shifters & More...



SPECIFICATIONS (Rev. A 07/14/26)

Frequency	470 - 940 MHz		
Insertion Loss (dB) *	Frequency (MHz)	Typ.	Max.
	470 - 940	0.13	0.40
	520 - 870	0.07	0.25
Amplitude Unbalance (dB)	Frequency (MHz)	Typ.	Min.
	470 - 940	1.0	1.4
	520 - 870	0.35	0.65
Phase Unbalance (Deg.)	Frequency (MHz)	Typ.	Min.
	470 - 940	2.1	4.5
	520 - 870	1.8	3.5


Isolation (dB)	Frequency (MHz)	Typ.	Min.
	470 - 940	22	19
	520 - 870	22	19
Power Rating	100 Watts Avg. (CW)		
Impedance	50 Ohms (Nom.)		
VSWR	Frequency (MHz)	Max.	
	470 - 940	1.4:1	
	520 - 870	1.4:1	
Operating Temperature Range	-55 to +85 °C		
* Is the average of the two coupling signals in excess of the 3 dB theoretical signal splitting			

90° HYBRID COUPLER

SYNSTRI[®] MODEL: MSQ4794M

WIDE BANDWIDTH

470 - 940 MHz




90° HYBRID COUPLER

SYNSTRIP® MODEL: MSQ4794M

WIDE BANDWIDTH

470 - 940 MHz

Data @ 25°C



PERFORMANCE PLOTS


90° HYBRID COUPLER

SYNSTRI[®] MODEL: MSQ4794M

WIDE BANDWIDTH

470 - 940 MHz

Data @ 25°C



PERFORMANCE PLOTS


90° HYBRID COUPLER

SYNSTRIIP® MODEL: MSQ4794M

WIDE BANDWIDTH

470 - 940 MHz

Data @ 25°C



PERFORMANCE PLOTS